

GP Batteries

PRODUCT SPECIFICATION

**GP GaN 65W Charger (3-port)
Model: GM3B**

Revision History

| Revision | Date | Initiator | Reason for Change |
|----------|-------------|-----------|-------------------|
| 0.0 | 12 Apr 2024 | CC Li | First release |
| | | | |
| | | | |
| | | | |
| | | | |

| | |
|--------------------|--------------------|
| Prepared By | Approved By |
| CC Li | Joyce Tse |
| Date: 12 Apr, 2024 | Date: 12 Apr, 2024 |



Member
Gold Peak Group

Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

Product Specification

Model no.: GM3B

| | | |
|---|--|--|
| <p>2 pins folded</p> <p>2 pins unfolded</p> | | |
| <p>GaN 65W Charger (3-port)</p> | <p>Interchangeable adapters BS, GS</p> | <p>2m USB-C to USB-C cable (65W) & Cable tie</p> |

| | |
|-----------------------------------|---|
| Product Name | : 65W GaN Charger (3-port) |
| Description | : 65W GaN Charger (3-port) |
| Application | : Charge laptops, mobiles, tablets, cameras, Switch etc |
| Number of USB ports | : USB-C x 2, USB-A x 1 |
| Input | : AC 100-240V, 50/60Hz, 1.5A Max. |
| Output | : USB-C1/C2: DC 5.0V/3.0A, 9.0V/3.0A, 12.0V/3.0A, 15.0V/3.0A, 20.0V/3.25A PPS: 3.3-11V/3.0A USB-A: DC 4.5V/5.0A, 5.0V/4.5A, 9.0V/3.0A, 12.0V/2.5A, 20.0V/1.5A |
| Total output power | : 65.0W Max. |
| Over current protection (OCP) | : Yes |
| Short circuit protection (SCP) | : Yes |
| Over temperature protection (OTP) | : Yes |
| Operation Temperature | : 0°C to 25°C |
| Storage Temperature | : -10°C to 70°C |
| Product Dimension (+/-0.5mm) | : 58.6 (L) x 47 (W) x 29.5 (H) mm (Plugs excluded) |
| Weight | : 110g (Plugs excluded) |
| Compliance | : CE-LVD, CE-EMC, ErP, ROHS, REACH |
| Bundle Accessories | : 2m USB-C to USB-C cable (65W) / Cable tie |
| Warranty Period | : 12 months from ex-factory date |