



PRODUCT SPECIFICATION

Recyko Charge 10 Ultra-Fast NiMH Charger Model : S491

Revision History

Revision	Date	Initiator	Reason for Change
0.0		CC Li	Initial release

Prepared By	Approved By
CC Li	Vincent Lam
Date: 2021/11/03	Date: 2021/11/03




Member
Gold Peak Group

Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.

GP Batteries

Product Specification

Model no.: S491



Product Name	: 4-Slot NiMH Charger S491
Input	: 100-240Vac, 50/60Hz, 85W
Charging Channels	: 4 independent channels ; 1 slot/channel for 1-4 pcs AA/AAA NiMH batteries
Output Voltage	: 1.6Vdc
Charging Current	: Ultra-fast mode - 10A/5A/3.5A each for 1-4 pcs AA ; 1.5A/0.75A each for 1-4 pcs AAA ECO mode – 600mA each for 1-4 pcs AA ; 300mA each for 1-4 pcs AAA

Charging Time :

DC 4 x 1.6V 0.3-10A	Range (Size)	Capacity (mAh)	Quantity	Charging time	
				Ultra-fast charging mode	Eco charging mode
	Charge 10 battery (AA)	1,700		10mins**	200min
	Recyko / Recyko Pro battery (AA)	1,300-2,600	1-4pcs	15-35mins	160-320min
	Recyko / Recyko Pro battery (AAA)	650-950		28-45mins	160-230min

^ Approximate charging time is based on the same battery size and capacity at ambient temperature (20°C).

The charging completion time of each batteries in the charger may have a few minutes difference.

** Charges 1-4pcs of Recyko Charge 10 AA 1700mAh to 90%+ of capacity at 20°C using Ultra-fast charging mode in 10mins.

Trickle Charging Current : 60mA approx. for AA ; 30mA approx. for AAA

GP Batteries

Product Specification

Model no.: S491

LED Indication :

Charging Condition	Four Tri-Color LED (Blue/Green/Red)
Power On	Blue/Green Slow Flash Alternatively
Charging	Blue/Green Breathing on-off at Ultrafast/ECO Mode
Fully charged	Blue/Green Steadily On at Ultrafast/ECO Mode
Bad/Primary Batteries inserted	Red LED Fast Flashing
Temperature Cutoff (TCO)	Blue/Red flash alternatively in Ultrafast Mode Green/Red flash alternatively in ECO Mode
System Warning	Blue/Green/Red Flash alternatively

Safety protection : 1) Fixed Timer – 60min for AA, 100min for AAA in Ultrafast mode
350min for AA & AAA in ECO mode

2) -dV

3) TCO 58+/-2C

Operation Temperature : 0°C to 35°C

Dimensions : 155mm (L) x 92mm (W) x 35mm (H) (exclude AC plug)

Weight : 235g

Certification : EMC, IEC60335, UKCA & Rohs

Warranty Period : 12 months from ex-factory date



Member
Gold Peak Group