

# PRODUCT DATA SHEET - FDV

Extinguisher Model LITHEX25



### Area of use

The unique properties of AVD allow the extinguishing agent to be used in various areas, especially in fire containment. CGS AVD extinguishing units are effective against fires in lithium-ion batteries over 750 Wh, such as larger installations, server rooms, and operations handling batteries and modules. Suitable for industry, retail operations, public services, mechanical workshops, residential areas, warehouses, airports, ports, recycling stations, hospitals, battery collection, etc

### Function of the agent

AVD cools down the burning material, smothers the fire by creating a temperature-resistant layer that prevents oxygen supply. If the batteries are built into a product, there is a risk of limited extinguishing effect as the extinguishing agent may not cool down the batteries.



## TECHNICAL SPECIFICATION

Extinguisher Efficiency Class	13A	Skü	600234
Extinguisher Fire Class	A	EAN	7320896002340
Extinguisher Operational Temperature	5 °C / +60 °C	Extinguisher Certification	CE, EN1866-1
Extinguisher Size	25 L	Extinguisher Model	LITHEX25
Extinguisher Discharge Time	210 sek.		
Extinguisher Pressure	8 bar		
Extinguisher Cylinder Material	Steel		

fdv\_important\_extinguisher

For more information contact: GPBM Nordic AB  
Telephone: +46 31 799 16 00  
[www.gpbmnordic.se](http://www.gpbmnordic.se)

